

Name: \_\_\_\_\_ Date: \_\_\_\_\_ Event: \_\_\_\_\_ Ambient Temp: \_\_\_\_\_

Track: INDOOR  OUTDOOR  Size: SMALL  MEDIUM  LARGE  Traction: LOW  MEDIUM  HIGH

Surface: SMOOTH  BUMPY  RUTTED  Type: LOOSE / LOAMY  HARD PACKED  BLUE GROOVE  CLAY  ASTRO

Ackerman/Bumpsteer/Arm Plate/Spindle Height/Servo Saver Condition: DUSTY  DRY  WET  MUDDY

WASHERS:

WASHERS:

WASHERS:

PLATE: **ABCDEFGHIJ**

SPINDLE PART#

TKR9141 (+1,0)

TKR9141B (-1, -2)

FULL TURNS FROM FULLY TIGHT

(FRONT) (REAR) SWAY BAR BUSHINGS

## Front End:

TOWER

UNI/CVD

U - TKR9487

C - TKR9472

STANDOFF

0mm +2mm +4mm

OFFSET

2mm 3mm 4mm

"A" Block:

TKR9461 (0mm)

TKR9461B (-1mm)

## Suspension:

RIDE HEIGHT:	CAMBER:
CASTER BLOCK:	SWEEP:
KICK UP:	TOE:
SWAY BAR:	SHOCK LENGTH:
UP TRAVEL LIMITERS:	DROOP:
OIL:	BRAND:
PISTON:	SPRING:
REBOUND:	BUILD:

"B" Block:

TKR9462 (0mm)

TKR9462B (-1mm)

## Differentials:

OPTION	FRONT	CENTER	REAR
<b>Diff Oil</b>			
(TKR5144B)	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
(TKR5144)	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
(TKR5145B)	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
(TKR9145)	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
Standard (TKR9114-TKR9112)	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
Lightened (TKR5114XB-TKR5112x)	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
(TKR9150)	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
(TKR9150B)	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
(TKR9115C)	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
(TKR9115B)	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
(TKR9149)	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
(TKR9149A)	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>

## Rear End:

TOWER

UNI/CVD

U - TKR9487

U - TKR9687

C - TKR9472

STANDOFF

0mm +2mm +4mm

REAR HUB

OFFSET

2mm 3mm 4mm

-2mm 0mm +2mm

REAR HUB

"C" Block:

Screw (TKR1324)

## Suspension:

RIDE HEIGHT:	CAMBER:
ANTI-SQUAT:	TOE:
SWAY BAR:	SHOCK LENGTH:
UP TRAVEL LIMITERS:	DROOP:
OIL:	BRAND:
PISTON:	SPRING:
REBOUND:	BUILD:

## Chassis Braces:

MIDDLE:  REAR:

## Tires / Wheels:

BRAND / TREAD:

COMPOUND:

INSERT:

WHEEL:

NOTES:

## Body / Wing:

BODY MAKE:

WING MAKE:

WING MOUNT POSITION:

0mm:  +7mm:  +12mm:

NOTES:

## Bulkheads:

FRONT REAR

TKR9416 (0mm)  TKR9416 (0mm)

TKR9416B (-2mm)  TKR9416B (-2mm)

## Drivetrain:

PINION / SPUR: \_\_\_\_\_ / \_\_\_\_\_ (teeth)

## Equipment:

ESC: \_\_\_\_\_ MOTOR: \_\_\_\_\_

BATTERY: \_\_\_\_\_ SERVO: \_\_\_\_\_

## Notes:

## Wheelbase:

REAR FRONT

(Shims)

(Thick - 2mm)

(Thin - 1mm)